

PT-4000i Specifications

The PT-4000i Series Integrated Touch Screen System is a complete self contained unit designed to simplify system integration with more functionality, performance, durability and reliability.

With its expansion capabilities, connection with peripherals can be maximized. The system can work in stand alone or networked environments. It's dirt and spill resistant design provides reliable operation even in harsh environments.

The System includes all of the features required to provide VARS, Integrators and OEM's with a complete hardware solution.

Model(s)	PT-4000i	PT-4100i
CPU	Intel Celeron 733 Mhz+ or PIII 850 Mhz	
Memory	128 Mb expandable to 512 Mb	
Flash memory	DiskOnChip expandable to 288 Mb (Optional)	
Hard Drive Storage	UltraDMA 3.5" IDE or 2.5" IDE HDD	
Video RAM	4 Mb	
Display	Color LCD 12.1" TFT 800 x 600	Color LCD 13.3" TFT 1024 x 768
Touch Panel	5-wire Resistive or Capacitive	
Dual Display	Dual independent video output	
LED Indicators	5 LED (HDD, KB status and power)	
IR Keyboard	Built-in receiver	
Power Supply	AC 115V/230V external power supply	
I/ O Ports	<ul style="list-style-type: none"> · 4 RS232 ports, 3 external D-sub 9 with 5/12VDC · 1 Parallel Port · 1 Ethernet 10/100 Base-T · 1 PS/2 KB Port · 1 PS/2 Mouse Port · 1 SVGA Port (CRT support to 1024x768) · 2 Cash Drawer port (24VDC) · 2 USB Ports · Audio Out 	
Operating System(s)	DOS, Windows95/98/NT/ 2000/Me, OS/2, Unix, Linux	
Certifications for Safety and EMI	UL, CUL, FCC, CE, VCCI Class A	
Dimensions	WxDxH: 12.8" x 13.4" x 12.4" (325mm x 340mm x 315mm) Package size: 18.3"x23.2"x16.3"	
Weight	Net: 7.2Kg / 15.9 Lb Gross: 12.8Kg / 28.2 Lb	

Options

- Magnetic card reader (1,2 or 3 tracks)
- Barcode reader
- Rear customer display
- Pole display
- Internal floppy drive or CD-ROM drive
- Internal Smart Card reader
- Smart Card
- Micro PCI