

EVO

TP4 TruFlat POS Terminal

The EVO TP4 TruFlat sets a whole new standard by offering enterprise-class build quality, resistive or projected capacitive touchscreen technologies, and the latest in high-performance Intel® processors. Available with Atom™, Celeron™, Pentium™, or Core i3™ Dual-Core processors, the EVO TP4 thrives in the most demanding environments. Achieving an IP54 certified rating, the EVO TP4 is both dust and splash resistant.



Shown with optional MSR



Shown with optional customer display

Key Features



Dual-Core Processors

Available with Intel Atom, Celeron, Pentium or Core i3



Touchscreen

15" (381mm) zero bezel, 5-wire resistive or PCAP touchscreen technology



Hard Drive

2.5" (64mm) 250GB HDD or 60-120GB SSD



Built In Cable Management

Keeps cords out of sight



EZHD Slot

Makes for quick HDD or SSD replacement



IP54 Rating

Resistant to dust buildup and splashing water



Sturdy Die-Cast Aluminum Alloy Frame

Provides bump-free operation



Optional Accessories

Optional integrated MSR, VFD customer display, 8.4" (213mm) rear LCD display, 15" (381mm) rear LCD display, or Biometric Reader

■ POS-X Warranty

Industry-leading Warranty Protection

- 3 year warranty
- *2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

*Available in USA and Canada

■ POS-X Service and Support

24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

5-WIRE RESISTIVE MODELS	EVO-TP4C-D	EVO-TP4C-C	EVO-TP4C-P	EVO-TP4C-3
PCAP MODELS	EVO-TP4D-D	EVO-TP4D-C	EVO-TP4D-P	EVO-TP4D-3
Processor	Intel® Atom D2550 1.86GHz Dual Core	Intel® Celeron G530 2.4GHz Dual Core	Intel® Pentium G850 2.9GHz Dual Core	Intel® Core i3-2120 3.3GHz Dual Core
Chip Set	CPU with Graphic built-in + ICH 8M	GHz Dual Core Intel® Q67 PCH, 6.1W (AMT/RAID enabled)		
System Memory	2 x DDR3 2GB to 4GB	1 x DDR3 DIMM 2GB to 8GB		
Hard Drive	250GB HDD or 60-120GB SSD			
Graphic Memory	Integrated Intel® GMA® 3650, DX9	Intel® HD Graphics 3000/2000		
GigaLAN (10/100/1000)	1 x RJ45			
Weight (w/base)	15 lbs (6.8kg)	15.4 lbs (7kg)		
Electrical	90W/19V	120W/19V		
PORTS		ENVIRONMENTAL		
Parallel	1	Ingress Protection Rating	IP54-Resistant to dust buildup and splashing water	
USB 2.0	5 (1 is dedicated to MSR)	Operating Temperature	32°F to 95°F (0°C to 35°C)	
Serial	4 x RJ45 COM4 with 5V/12V	Humidity	20% to 80% non-condensing	
VGA	1 x DB15 Female	Warranty	3-year warranty with free *2-day Advance Exchange Service	
Cash Drawer Port	1 x RJ11	Certifications	FCC, Class A, CE, LVD, RoHs, NOM	
Speakers	2 x 2W Stereo	Supported OS	POS Ready 2009 & 7/Win 7 Pro/ Available with no O/S	
Hard Drive	2.5" (64mm) Easy Access Slot: 250GB HDD or 60-120GB SSD	OPTIONAL ACCESSORIES		
PHYSICAL		EVO-MR4	3 Track Magnetic Stripe Reader with USB interface	
Housing	Die Cast Aluminum	EVO-BR4	Integrated Bio Reader	
Dimensions (w/base) (WxDxH)	14.21" x 9.76" x 13.27" (361mm x 248mm x 337mm)	EVO-RD4-VFD	Integrated 2x20 VFD Customer Display	
VESA Wall Mountable	3.9" x 3.9" (100mm x 100mm)	EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD w/VGA Cable & Mount	
Tilt Angle	0° – 90°	EVO-RD4-LCD15	Integrated Rear Display, 15" (381mm) LCD w/VGA Cable and Mount	
Housing Color	Black	EVO-XZ4-M100	Universal VESA Mount for All Terminals and Touch Monitors	
Bezel	TruFlat Zero Bezel	WARRANTY EXTENSION AND UPGRADES		
LCD Display	15" (381mm) LED LCD	ZWE-TPC	2-Year Warranty Extension	
Resistive Touch (TP4C)	5-Wire Resistive	ZOE-TPC3	*3-Year Overnight Exchange	
PCAP Touch (TP4D)	Projected Capacitive Touch (PCAP)	ZOE-TPC5	*5-Year Overnight Exchange	

*Available in USA and Canada



1975 Midway Lane, Suite O
 Bellingham, WA 98226
 sales@pos-x.com
 360.738.8433
 www.pos-x.com

DS-EVOTP4 REV 0114

